

 <p>THIEL TOOL & Engineering Co., Inc. 314.241.6121 www.thieltool.com</p> <p>PRESS SPECIFICATIONS</p>	1 STRAIGHT SIDE, SOLID BED MINSTER 600	2 C-FRAME, CUSHION VERSON 105	3 STRAIGHT SIDE, NO WINDOW DANLY 250	4 C-FRAME, CUSHION VERSON 150	7 STRAIGHT SIDE, SOLID BED MINSTER 150	8 STRAIGHT SIDE, CUSHION MINSTER 100	10 STRAIGHT SIDE, SOLID BED MINSTER 300	14 STRAIGHT SIDE, CUSHION MINSTER 200	15 STRAIGHT SIDE BROWN BOGGS 800	16 STRAIGHT SIDE, CUSHIONS VERSON 400	34 STRAIGHT SIDE, CUSHION VERSON 500	36 STRAIGHT SIDE, SOLID BED BLISS 500	40 STRAIGHT SIDE, SOLID BED BLISS 300	
	BOLSTER													
	Thickness (inches)	7.000	4.120		4.375	6.005	5.010	7.000	7.012	9.000	8.500	8.010	10	5.950
	Size L-R x F-B (inches)	120 x 54	39 x 30	48 X 36	50 x 30	54 x 40	48 x 31	84 x 48	60 x 44	144 X 60	131 x 60	96 x 60	108 x 54	42 x 36
	Die Mounting	T-Slots	Tapped Holes	T-Slots	Tapped Holes	T-Slots	T-Slots	T-Slots	T-Slots	T-Slots	T-Slots	T-Slots	T-Slots	Tapped Holes
	RAM													
	Stroke (inches)	12	8	12	8	6	4	12	6	14	16	10	9	12
	Size L-R x F-B (inches)	120 x 54	29.5 x 28	48 X 36	34 x 24	48 x 23	48 x 18.5	84 x 48	60 x 25	144 x 60	130 x 60	96 x 60	108 x 54	36 x 36
	Die Mounting	T-Slots	Tapped Holes	T-Slots	Tapped Holes	T-Slots	Tapped Holes	T-Slots	Tapped Holes	T-Slots	T-Slots	T-Slots	T-Slots	Tapped Holes
	SHUT HEIGHT To Bolster (inches)	17-27	10-14	13-25	11.5-17.5	13-17	11-15	17-23	13-19	20-32	22-28	17-23	11-23	11-23
SPEED (S.P.M.)	0-60	35	30	35	50-90	60-160	40-80	50-100	15-40	12-24	25-50	40-80	25	
FEED CAP.														
Press Window (H x W)	15 x 33	C-Frame	No Window	C-Frame	14 x 20.125	11.5 x 16.125	15 x 25.125	14 x 22	39.875 x 54	17.5 x 39	25.125 x 39.75	19.875 x 34	21 x 27.75	
Thickness (inches)	.030-.250	N/A	N/A	.030-.105	.010-.110	.090-.156	.030-.375	.030-.332	.025-.360	.025-.360	.030-.312	.030-.375	.010-.045	
Width (inches)	1-24	N/A	N/A	1-12	1-12	1-12	1-24	1-12	1-36	1-36	1-24	1-24	1-24	
Max. Coil Size (#)	15,000	N/A	N/A	2,000	4,000	4,000	10,000	8,000	30,000	40,000	20,000	10,000	6,000	